



# <u>DSPPA-Audio Price List – Feb 2024 – P1</u> <u>Speakers</u>

NO	Model	Description	Picture	Price
1	DSP3011	3W/6W, 3" Spot Ceiling Speaker , Frame Less ABS White grille , ideal choice for commercial applications in hotel, school, office and factory, Spring clip for easy installation  •Power Input:70v/100v  •Rated power: 3/6W  •Sensitivity: 88dB±2dB  •Max SPL: 95dB±2dB  •Freq. Response: 120Hz ~ 20kHz  •Driver units: 3"x1  •Outline dimension: 104mm*79mm  •Net weight: 0.4kg		640
2	DSP3011 C	Outdoor & Heat Resistance -6W, 3" Spot Ceiling Speaker, Frame Less ABS White grille, With IP66 waterproof structure design and simple appearance modeling  • Power Input:70/100v  • Rated power: 3/6W  • Sensitivity: 87dB±2dB  • Max SPL: 94dB±2dB  • Freq. Response: 300Hz ~ 20kHz  • Driver units: 3"x1  • Outline dimension: 125mm*93mm  • Net weight: 0.5kg		800
3	DSP124	3W/6W, 6" Ceiling Speaker , ABS White grille , ideal choice for industrial and commercial applications in hotel, school, office and factory, Spring clip for easy installation  •Power Input:70v/100v  •Rated power: 3/6W  •Sensitivity: 96±2dB  •Max SPL:98±2dB  •Freq. Response: 83Hz-18kHz  •Driver units: 6.5"x1  •Mounting Hole : ø165~ø170mm  •Outline dimension& weight: 186mm*70mm& 0.5kg	SSAFE	665





	انظمة أمنية	<u> DSPPA-Audio Price List – Feb</u>	2024 - PI	
4	WAT- 6311 watania	3W/6W, 6" Ceiling Speaker Frame Less, Aluminum grille, Ideal for Home, Gym, Store, Iounge, school, office, hotel & airport background music system, Spring clip for easy installation.  •Power Input:70v/100v •Rated power: 3W-6W •Sensitivity: 95±2dB •Max SPL:103±2dB •Freq. Response: 90Hz-20kHz •Driver units: 6.5"x1 •Mounting Hole: ø165~ø170mm •Outline dimension: 185 mm*70mm • Weight: 0.9kg		<b>690</b>
5	WAT- 6311L watania	6W, 6" Frame-less Ceiling Speaker(8Ω), Frame Less carbon alloy aluminum Grilldesign Fashionable design of thin edge, Suitable for hotel, shopping mall, supermarket, school, Spring clip for easy installation.  •Power Input:8Ω •Rated power:6W •Sensitivity: 95±2dB •Max SPL:103±2dB •Freq. Response: 90Hz-20kHz •Driver units: 6.5"x1 •Mounting Hole: ø165~ø170mm •Outline dimension& weight: 185 mm*74mm •Net weight: 0.9kg.	2005	650
6	DSP6011	3W/6W, 6" Ceiling Speaker Frame Less design, Aluminum grille, Ideal for Home, Gym, Store, Iounge, school, office, hotel & airport background music system, Spring clip for easy installation.  •Power Input:70v/100v •Rated power: 3W-6W •Sensitivity: 95±2dB •Max SPL:103±2dB •Freq. Response: 90Hz-20kHz •Driver units: 6.5"x1		750





	وانظمة أمنية	יבטועני <u>DSPPA-Audio Price List – Feb</u>	LULT II	
		●Mounting Hole : ø165~ø170mm		
		●Outline dimension& weight: 185 mm*70mm		
		■Net weight: 0.9kg		
		6W, 6" Frame-less Ceiling Speaker(8Ω), Frame Less carbon		
		alloy aluminum Grilldesign Fashionable design of thin		
		edge, Suitable for hotel, shopping mall, supermarket,	and some	
		school, Spring clip for easy installation .		
		●Power Input:8Ω	inspen )	
		●Rated power:6W		
7	DSP6011L	Sensitivity: 95±2dB		70
		●Max SPL:103±2dB		
		●Freq. Response: 90Hz-20kHz		
		●Driver units: 6.5"x1		
		●Mounting Hole: ø165~ø170mm		
		●Outline dimension& weight: 185 mm*74mm		
		■Net weight: 0.9kg		
		3W/6W, 6" Ceiling Speaker Frame Less design, Aluminum		
		grille , Ideal for Home , Gym , Store ,lounge , school, office,		
		hotel & airport background music system, Spring clip for		
		easy installation.		
		●Power Input:70v/100v		
	DSP6011B	●Rated power: 3W-6W		
8		●Sensitivity: 95±2dB		78
	Black	●Max SPL:103±2dB	.1060PM	
		●Freq. Response: 90Hz-20kHz		
		●Driver units: 6.5"x1		
		●Mounting Hole : ø165~ø170mm		
		●Outline dimension& weight: 185 mm*70mm		
		●Net weight: 0.9kg		
		3W/6W, 6" Ceiling Speaker Frame-less design, 6.5 carbon		
		alloy &aluminum Grill, Ideal for Home , Gym , Store ,lounge		
		, school, office, hotel & airport background music system,		
9	DSP5011	UV level Flam retarding, Spring clip for easy installation.		79
		●Power Input:70v/100v		
		Rated power:3/6W		
		●Sensitivity: 95±2dB		





	المصوب المتتب	DOTTA Addition The List Top 1		
		●Max SPL:103±2dB		
		●Freq. Response: 65Hz-20kHz		
		●Driver units: 6.5"x1		
		<ul><li>Mounting Hole : ø165~ø170mm</li></ul>		
		●Outline dimension: 190.5mm*70mm & 0.75kg		
		6W (8Ω), 6" Frame-less Ohm Ceiling Speaker, Frame Less		
		carbon alloy &aluminum Grilldesign Fashionable design of		
		thin edge, plane, and big cylinder, Suitable for hotel,		
		shopping mall, supermarket, school, UV level Flam		
		retarding, Spring clip for easy installation.		
		●Power Input:8Ω	Dave Oca	
10	DCDF0111	●Rated power:6W		755
10	DSP5011L	●Sensitivity: 90±2dB	-	/55
		●Max SPL:97±2dB		
		●Freq. Response: 110Hz-15kHz		
		●Driver units: 6.5"x1		
		●Mounting Hole: ø165~ø170mm		
		●Outline dimension: 190.5mm*70mm		
		■Net Weight : 0.60kg		
		Medium Size 1.5W/3W/6W, 4.5" Ceiling Speaker, High		
		Quality ABS White, ideal choice for industrial and		
		commercial applications in hotel, school, office and factory,		
		Spring clip for easy installation		
		●Power Input:70v/100v		
	DSP501	●Rated power: 1.5 ~ 6W		
11	D3F301	Sensitivity: 96±2dB		950
		●Max SPL:96±2dB		
		●Freq. Response: 75Hz-18kHz		
		●Driver units: 4.5"x1		
		●Mounting Hole: ø154~ø164mm		, /
		●Outline dimension& weight: 18mm*80mm		
		■Net Weight : 0.8kg		





12	DSP662	6W Ceiling Speaker with Iron Fire Dom, ABS White grille, ideal choice for industrial and commercial applications in hotel, school, office and factory  •Power Input:100v  •Rated power:6W  •Sensitivity: 91±2dB  •Max SPL:97±2dB  •Freq. Response: 80Hz-20kHz  •Driver units: 6.5"x1  •Mounting Hole: ø166~ø174mm  •Outline dimension& weight: 174mm*166mm  •Net Weight: 1.0kg.	EDENDER	1255
13	DSP107	15W, Pendant Type Speaker, ideal for large distance area and background noises, such as station, park, school, square, military camp, industrial park, etc.  • 70/100V, 8-15W, with multiple terminals  • Max SPL: 102±2dB  • Wide Freq.Resp.:110Hz-18kHz  • High sensitivity: 91±2dB  • Hanging style and the suspensory is adjustable  • Made of high quality industrial plastic  • Net weight: 2.0 kg.		3450
14	DSP107B Black	15W, Pendant Type Speaker, ideal for large distance area and background noises, such as station, park, school, square, military camp, industrial park, etc.  ●70/100V, 8-15W, with multiple terminals  ●Max SPL: 102±2dB  ●Wide Freq.Resp.:110Hz-18kHz  ●High sensitivity: 91±2dB  ●Hanging style and the suspensory is adjustable  ●Made of high quality industrial plastic  ● Net weight: 2.0 kg		3850





15	DSP207II	20W, Wall Mount Sound Projector Speakerdesign for Long transmission distance, ideal choice for tunnels, corridor and shopping galleries.  • 100v/70v transformer  • Coaxial design with 5 inch woofer and 0.75 inch tweeter  • Frequency Response: 90-20000Hz  • Max SPL: 98±2dB  • Sensitivity: 86±2dB  • Driver units: Woofer 5"× 1+ Tweeter 0.75"× 1  • can work continuously for 100 hours at rated  • Outline dimension: 218mm*138mm  • Net weight: 1.44kg.	3000
16	DSP5311	6W , Surface Mount 6 " Frame-less Ceiling Speaker , Ideal for school, office, hotel & airport  • Power Input:70/100v  • Rated power:6W (3-6W connectors)  • Sensitivity: 90±2dB  • Max SPL:100±2dB  • Freq. Response: 140Hz-16kHz  • Driver units: 6.5"x1  • Outline dimension: 203.5mm*94mm  • Net weight: 1.04kg.	1500
17	DSP5311 B Black	6W, Surface Mount 6 " Frame-less Ceiling Speaker, Ideal for school, office, hotel & airport  • Power Input:70/100v  • Rated power:6W (3-6W connectors)  • Sensitivity: 90±2dB  • Max SPL:100±2dB  • Freq. Response: 140Hz-16kHz  • Driver units: 6.5"x1  • Outline dimension: 203.5mm*94mm  • Net weight: 1.04kg.	1600





10W, 6.5" Frameless Ceiling Speaker, Frame Less design , Aluminum grille , Suitable for home , hotel , shopping mall, supermarket, school , UV level Flam retarding, Spring clip for easy installation .  • Power Input:70v/100v • Rated power: SW/10vW • Sensitivity: 89±2dB • Max SPL:100±2dB • Freq. Response: 70Hz-18kHz • Driver units: 6.5"x1 • Outline dimension: 185mm*74mm • Net weight: 0.94g.  10W, 6.5" Coaxial Frameless Ceiling Speaker, Frame Less design , Aluminum grille , Suitable for home , hotel, shopping mall , supermarket, school , UV level Flam retarding, Spring clip for easy installation . • Power Input:70/100v • Rated power:2.5W/5W/10W • Sensitivity: 93±2dB • Max SPL:10332dB • Freq. Response: 90Hz-18kHz • Driver units: 6.5"x1 , 0.75"x1 • Built-in coaxial Tweeter. • Outline dimension: 190mm*80mm • Net Weight : 1.0kg.  10W (80) , 6.5" Frame-less Ohm Ceiling Speaker, Frame Less carbon alloy & aluminum Grilldesign Fashionable design of thin edge, plane, and big cylinder , Suitable for hotel, shopping mall, supermarket, school, UV level Flam retarding, Spring clip for easy installation . • Power Input:80 • Rated power:10W • Sensitivity: 93±2dB • Max SPL:103±2dB		وأنظمة أمنية	<u> DSPPA-Audio Price List – Feb</u>	2027 11	
10W, 6.5" Coaxial Frameless Ceiling Speaker, Frame Less design , Aluminum grille , Suitable for home ,hotel, shopping mall, supermarket, school , UV level Flam retarding, Spring clip for easy installation .  Power Input:70/100v Rated power:2.5W/5W/10W Sensitivity: 93±2dB Max SPL:103±2dB Freq. Response: 90Hz-18kHz Driver units: 6.5"x1 , 0.75"x1 Built-in coaxial Tweeter. Outline dimension: 190mm*80mm Net Weight: 1.0kg.  10W (8Ω) , 6.5" Frame-less Ohm Ceiling Speaker, Frame Less carbon alloy &aluminum Grilldesign Fashionable design of thin edge, plane, and big cylinder , Suitable for hotel, shopping mall, supermarket, school, UV level Flam retarding, Spring clip for easy installation .  Power Input:8Ω Rated power:10W Sensitivity: 93±2dB Max SPL:103±2dB Freq. Response: 90Hz-18kHz	18	DSP7011	Aluminum grille, Suitable for home, hotel, shopping mall, supermarket, school, UV level Flam retarding, Spring clip for easy installation.  •Power Input:70v/100v •Rated power: 5W/10W •Sensitivity: 89±2dB •Max SPL:100±2dB •Freq. Response: 70Hz-18kHz •Driver units: 6.5"x1 •Outline dimension: 185mm*74mm		920
10W (8Ω), 6.5" Frame-less Ohm Ceiling Speaker, Frame Less carbon alloy &aluminum Grilldesign Fashionable design of thin edge, plane, and big cylinder, Suitable for hotel, shopping mall, supermarket, school, UV level Flam retarding, Spring clip for easy installation.  • Power Input:8Ω • Rated power:10W • Sensitivity: 93±2dB • Max SPL:103±2dB • Freq. Response: 90Hz-18kHz	19	DSP5211	10W, 6.5" Coaxial Frameless Ceiling Speaker, Frame Less design , Aluminum grille , Suitable for home ,hotel, shopping mall, supermarket, school , UV level Flam retarding, Spring clip for easy installation .  • Power Input:70/100v • Rated power:2.5W/5W/10W • Sensitivity: 93±2dB • Max SPL:103±2dB • Freq. Response: 90Hz-18kHz • Driver units: 6.5"x1 , 0.75"x1 • Built-in coaxial Tweeter. • Outline dimension: 190mm*80mm		1300
●Outline dimension:190mm*80mm●Net Weight : 1.0kg.	20	DSP5211L	10W (8Ω), 6.5" Frame-less Ohm Ceiling Speaker, Frame Less carbon alloy & aluminum Grilldesign Fashionable design of thin edge, plane, and big cylinder, Suitable for hotel, shopping mall, supermarket, school, UV level Flam retarding, Spring clip for easy installation.  •Power Input:8Ω •Rated power:10W •Sensitivity: 93±2dB •Max SPL:103±2dB •Freq. Response: 90Hz-18kHz •Driver units: 6.5"x1, 0.75"x1 tweeter		1200





		<u> DSPPA-Audio Price List – Feb</u>		1
		10W , Large Size, 6.5" Ceiling Speaker , High Quality ABS		
		White, ideal choice for industrial and commercial		
		applications in hotel, school, office and factory, Spring clip		
		for easy installation.		
		●Power Input: 70v/100v		
	DCDOO3	●Rated power: 1.5 ~ 10W		
21	DSP802	●Sensitivity: 92±2dB		1350
		●Max SPL: 100±2dB		
		●Freq. Response: 70Hz-18kHz		
		●Driver units: 6.5"x1		
		●Mounting Hole: ø180~ø190mm		
		●Outline dimension& weight: 210mm*80mm		
		●Net Weight : 0.8kg		
		10W ,Large Size, 6.5" Ceiling Speaker, High Quality ABS		
		White, ideal choice for industrial and commercial		
		applications in hotel, school, office and factory, Spring clip		
	DSP803	for easy installation.		1500
		●Power Input: 70v/100v		
		●Rated power: 1.5 ~ 10W		
22		●Sensitivity: 92±2dB		
		●Max SPL: 102±2dB		
		●Freq. Response: 80Hz-14kHz		
		●Driver units: 6.5"x1		
		●Mounting Hole: ø180~ø190mm		
		<ul><li>Outline dimension&amp; weight: 210mm*80mm</li></ul>		
		Net weight: 0.8kg		
		20W,Large Size coaxial Speajer 6.5" Coaxial Frameless		
		Ceiling Speaker, Narrow edge design, Aluminum grille,		
		Suitable for home ,hotel, shopping mall, supermarket,		
		school, UV level Flam retarding, Spring clip for easy		1
		installation .		
23	DSP703	●Power Input:70/100v		2550
		●Rated power:20W		
		●Sensitivity: 90±2dB		
		●Max SPL:101±2dB	**	
		●Freq. Response: 60Hz-18kHz		
		●Driver units: 6.5"x1 , 0.75"x1 tweeter		





	أنظمة أمنية	<u> DSPPA-Audio Price List – Feb</u>	<u> 2024 – PI</u>	
		<ul><li>◆Built-in coaxial Tweeter.</li><li>◆Outline dimension: 228mm*95mm</li><li>◆Net Weight: 1.8kg</li></ul>		
24	DSP8030	30W Coaxial In-ceiling Speaker with 8" Driver & Tweeter. Two-way ceiling speaker, wide diffusion angle, large output power, super-strong reproduction of voice and music. an ideal choice with superior sound quality.  •Power Input:70/100v •Rated power:30W •Sensitivity: 93±2dB •Max SPL:108±2dB •Freq. Response: 60Hz-18kHz •Driver units: 8"x1, 0.75"x1 tweeter •Outline dimension: 255mm*107mm •Net Weight: 1.6kg		2865
25	WAT1160 watania	6W Wall Mount Speaker ,Fashionable Appearances , Widely used for small-sized as classroom , store , meeting room , apartment ,etc., ABS environmental-friendly material, safe and durable  • Power Input:70v/100v • Rated power:6W (3-6W connectors) • made of ABS, safe and durable • Sensitivity: 90±2dB • Max SPL:100±2dB • Freq. Response: 108Hz-15kHz • Driver units: 4.5"x1 • Outline dimension: 228mm*188mm*101mm • Net weight: 0.8kg.		750
26	DSP116	6W Wall Mount Speaker ,Fashionable Appearances , Widely used for small-sized as classroom , store , meeting room , apartment ,etc., ABS environmental-friendly material, safe and durable  • Power Input:70v/100v  • Rated power:6W (3-6W connectors)  • made of ABS, safe and durable  • Sensitivity: 90±2dB		780
	Note : All	Prices Not Including VAT	350.000	





	متتوا موتيا	general Doilly radio lines list 1 on	
		<ul> <li>Max SPL:100±2dB</li> <li>Freq. Response: 108Hz-15kHz</li> <li>Driver units: 4.5"x1</li> <li>Outline dimension: 228mm*188mm*101mm</li> <li>Net weight: 0.8kg.</li> </ul>	
27	DSP117	10W Wall Mount Speaker ,Fashionable Appearances , Widely used for small-sized as classroom , store , meeting room , apartment ,etc., ABS environmental-friendly material, safe and durable  •Power Input:70v/100v •Rated power:6W (3W-6W connectors) •made of ABS, safe and durable •Sensitivity: 91±2dB •Max SPL:96±2dB •Freq. Response: 108Hz-14kHz •Driver units: 4.5"x1 •Outline dimension: 228mm*188mm*101mm •Net weight: 0.8kg .	890
28	DSP106II	10W Wall Mount Speaker ,Fashionable Appearances , Widely used for small-sized as classroom , store , meeting room , apartment ,etc., ABS environmental-friendly material, safe and durable  •Power Input:70v/100v •Rated power:10W (1.5-10W connectors) •made of ABS, safe and durable •Sensitivity: 92±2dB •Max SPL:100±2dB •Freq. Response: 160Hz-18kHz •Driver units: 4.5"x1 •Outline dimension: 228mm*188mm*101mm •Net weight: 0.8kg.	1200





	وانظمه امنيه	DSFFA-Audio Ffice List — I CD		
29	DSP406II	10WDecoratedWall Mount Speaker ,clever and beautiful enclosure made of high quality fiberboard manufacturing,  •Power Input:70v/100v  •Rated power:10W  •Sensitivity: 91±2dB  •Max SPL:99±2dB  •Freq. Response: 80Hz-18kHz  •Driver units: 4.5"x1  •Outline dimension: 302mm*205mm*115mm		1275
30	DSP203ii	<ul> <li>Net weight: 2.25kg.</li> <li>15W Two-way IndoorColumn Speaker, made of nylon high-fiber crystal with good permeability., ideal choice for commercial applications in the Indoorarea of hotel, school, office, restaurant, Mosque and church.</li> <li>Power Input:70v/100v</li> <li>Rated power:15W</li> <li>Sensitivity: 90±2dB</li> <li>Max SPL: 99±2dB</li> <li>Freq. Response: 140Hz-12kHz</li> <li>Driver units: 4"x2</li> <li>Outline dimension: 138×120×390mm</li> <li>Net Weight: 3.3kg.</li> </ul>	ne	2360
31	DSP403ii	30W Two-way IndoorColumn Speaker, made of nylon high- fiber crystal with good permeability., ideal choice for commercial applications in the Indoorarea of hotel, school, office, restaurant, Mosque and church.  •Power Input:70v/100v •Rated power:30W •Sensitivity: 94±2dB •Max SPL: 108±2dB •Freq. Response: 140Hz-12kHz •Driver units: 4"x4 •Outline dimension: 138×120×682mm •Net Weight: 5.3kg.		4100





32	DSP311B	20W, 180° Rotation Wall mount Speaker, ABS Black grille. built-in 4.5"+2" two ways speaker driver  • Built-in 100vtransformer  • Made of high quality engineering plastic  • Long-term durability, sound clear and sonorousness  • Rated power output at 20W  • High sensitivity(89±2dB)  • Freq. Range 80Hz-20kHz  • Equipped with hanging holes for mounting.	2800
		●Outline dimension: 215mm*170mm*150mm ●Net weight: 2.2kg	
33	DSP312B	30W, 180° Rotation Wall mount Speaker, ABS Black grille, built-in 4.5"*2" two ways speaker driver  Built-in 100v transformer.  Made of high quality engineering plastic.  Long-term durability, sound clear and sonorousness  Rated power output at 30W  High sensitivity(90±2dB)  Freq. Range 75Hz-20kHz  Equipped with hanging holes for mounting  Outline dimension: 242mm*182mm*162mm  Net weight: 3.5kg	3600
34	DSP320	20W Outdoor Wall mount Speaker.  Power Input:70V/100V  IP66 waterproof level  3"×1 full-range driver  High-class resin material.  Max. SPL:96±2dB  Freq. Resp.: 180Hz ~ 20kHz  Outline dimension: ø100mm *172mm  Net weight: 0.8kg.	1900





35	DSP8062	20W Speaker, High Quality Wall Mount Speaker with Power Tap, 180° Rotation, Pure Aluminum grille and ABS enclosure, ideal for industrial and commercial applications in hotel, school, Mosque, church, office and factory  •Power Input: 70v/100v/8Ω with power tap.  •Rated power: 20W (4-8-15-20W-8Ω stepping).  •Sensitivity: 90±2dB.  •Max SPL: 103±2dB.  •Freq. Response: 95Hz-20kHz.  •Driver units: 4" woofer x1 & 1" Tweeter x1.  •Outline dimension: 255mm*176mm*170mm  •Net weight: 2.6kg		3500
36	DSP8063	30W Speaker, High Quality Wall Mount Speaker with Power Tap, 180° Rotation, Pure Aluminum grille and ABS enclosure, ideal for industrial and commercial applications in hotel, school, Mosque, church, office and factory  •Power Input: 70v/100v/8Ω with power tap.  •Rated power:30W (2-4-8-15-30W-8Ω stepping)  •Sensitivity: 90±2dB  •Max SPL:105±2dB  •Freq. Response: 80Hz-20kHz  •Driver units: 5" woofer x1 & 1" Tweeter x1.  •Outline dimension: 280mm*194mm*185mm  •Net weight: 3.2kg.		3900
37	DSP8064	40W Speaker, High Quality Wall Mount Speaker with Power Tap, 180° Rotation, Pure Aluminum grille and ABS enclosure, ideal for industrial and commercial applications in hotel, school, Mosque, church, office and factory  •Power Input: 70v/100v/8Ω with power tap.  •Rated power:40W (2-4-8-15-30W-8Ω stepping)  •Sensitivity: 91±2dB  •Max SPL:107±2dB  •Freq. Response: 65Hz-20kHz  •Driver units: 6.5" woofer x1 & 1" Tweeter x1.  •Outline dimension: 310mm*215mm*203mm  •Net weight: 34.6kg.		4350





انظمة امنية	<u> DSPPA-Audio Price List – Feb</u>		
DSP7043	30WWaterproof Speaker, High Quality Wall Mount Speaker with Power Tap, 180° Rotation and robust design suits a variety of commercial interiors. Ideal for single-source audio in smaller venues, or straightforward integration into multi arrays.  • Power Input: 70v/100v/8Ω with power tap. • Rated power:30W (3-7.5-15-30W-8Ω stepping) • Sensitivity: 86±2dB • Max SPL:105±2dB • Freq. Response: 75Hz-20kHz • Driver units: 4.5" woofer x1 & 1" Tweeter x1 • Outline dimension: 230mm*155mm*148mm • Net weight: 3.2kg .		4850
DSP255II	High End Decorated30W Two-way Waterproof Column Speaker With Power Tap, power adjustable, ideal choice for Home& commercial applications in the outdoor area of hotel, office, restaurant, Mosque, church.  • Power Input: 70v/100v/8Ω with power tap.  • Rated power: 30W (2-4-8-15-30W-8Ω stepping) .  • Sensitivity: 87±3dB.  • Max SPL: 102±3dB.  • Freq. Response: 140Hz-20kHz.  • Driver units: Woofer 2X3", Tweeter 1X1".  • Outline dimension: 376×109×102 mm		5800
DSP455II	High End Decorated60W Two-way Waterproof Column Speaker With Power Tap, power adjustable, ideal choice for Home& commercial applications in the outdoor area of hotel, office, restaurant, Mosque, church.  •Power Input: 70v/100v/8Ω with power tap. •Rated power: 60W (5-10-20-40-60W-8Ω stepping) •Sensitivity: 89±3dB. •Max SPL: 107±3dB. •Freq. Response: 140Hz-20kHz. •Driver units:Woofer 4X3", Tweeter 1X2". •Outline dimension: 606 × 109 × 102 mm •Net Weight: 4 kg.		8300
	DSP7043	SOWWaterproof Speaker, High Quality Wall Mount Speaker with Power Tap, 180° Rotation and robust design suits a variety of commercial interiors. Ideal for single-source audio in smaller venues, or straightforward integration into multi arrays.    Power Input: 70v/100v/8Ω with power tap.	30WWaterproof Speaker, High Quality Wall Mount Speaker with Power Tap, 180° Rotation and robust design suits a variety of commercial interiors. Ideal for single-source audio in smaller venues, or straightforward integration into multi arrays.  Power Input: 70v/100v/8Ω with power tap.  Rated power:30W (3-7.5-15-30W-8Ω stepping)  Sensitivity: 86±2dB  Freq. Response: 75Hz-20kHz  Ortine dimension: 230mm*155mm*148mm  Net weight: 3.2kg.  High End Decorated30W Two-way Waterproof Column Speaker With Power Tap, power adjustable, ideal choice for Home& commercial applications in the outdoor area of hotel, office, restaurant, Mosque, church.  Power Input: 70v/100v/8Ω with power tap.  Rated power: 30W (2-4-8-15-30W-8Ω stepping).  Sensitivity: 87±3dB.  Freq. Response: 140Hz-20kHz.  Ortiver units: Woofer 2X3", Tweeter 1X1".  Outline dimension: 376×109×102 mm  Net Weight: 3.0 kg.  High End Decorated60W Two-way Waterproof Column Speaker With Power Tap, power adjustable, ideal choice for Home& commercial applications in the outdoor area of hotel, office, restaurant, Mosque, church.  Power Input: 70v/10v/8Ω with power tap.  Rated power: 60W (5-10-20-40-60W-8Ω stepping)  Sensitivity: 89±3dB.  Max SPL: 107±3dB.  Freq. Response: 140Hz-20kHz.  Oriver units: Woofer 4X3", Tweeter 1X2".  Outline dimension: 606×109×102 mm





41	DSP108	10W Two-way Waterproof Column Speaker, Made of aluminum never rust or corrosion, ideal choice for industrial and commercial applications in the outdoor area of hotel, school, office, restaurant and factory, Mosque, church.  • Power Input:70v/100v • Rated power:10W (5-10 connectors) • Sensitivity: 87±2dB • Max SPL:97dB • Freq. Response: 140Hz-14kHz • Driver units: 4"x1, 2.5"x1 • Outline dimension: 310mm*150mm*125mm • Net weight: 2.3kg.	2750
42	DSP208	20W Two-way Waterproof Column Speaker, Made of aluminum never rust or corrosion, ideal choice for industrial and commercial applications in the outdoor area of hotel, school, office, restaurant and factory, Mosque, church.  •Power Input:70v/100v •Rated power:20W (10-20W connectors) •Sensitivity: 89±2dB •Max SPL: 102±2dB •Freq. Response: 140Hz-14kHz •Driver units: 4"x2, 2.5"x1 •Outline dimension: 410mm*150mm*125mm •Net Weight: 3.3kg.	 3950







43	DSP308	30W Two-way Waterproof Column Speaker, Made of aluminum never rust or corrosion, ideal choice for industrial and commercial applications in the outdoor area of hotel, school, office, restaurant and factory, Mosque  •Power Input:70v/100v  •Rated power:30W (15-30W connectors)  •Sensitivity: 91±2dB  •Max SPL: 106±2dB  •Freq. Response: 140Hz-14kHz  •Driver units: 4"x3, 2.5"x1  •Outline dimension: 510mm*150mm*125mm  •Net Weight: 4.3kg.	4100
44	DSP643	20W Landscape Garden Waterproof Rock Speaker, Heavy damage proof finish.  Power Input:70V/100V  Power taps at 10W-20W@100V  IP66 waterproof level  6.5"×1 full-range driver  High-class resin material.  Max. SPL:100±2dB  Freq. Resp.: 100Hz ~ 15.5kHz  Outline dimension:380mm*320mm*250mm  Net weight: 5kg.	5300
45	DSP310	20W Outdoor Landscape Garden Speakers  Power Input:70V/100V  IP66 waterproof level  3"×1 full-range driver  High-class resin material.  Max. SPL:96±2dB  Freq. Resp.: 180Hz ~ 20kHz  Outline dimension: ø100mm *172mm  Net weight: 0.8kg.	1900





46	DSP1130	<ul> <li>30W Horn Speaker Waterproof Speaker, made of High Quality ABS</li> <li>Waterproof, IP66.</li> <li>Rated power: 30W (5-10-15-30W-8Ω stepping).</li> <li>Input signal: 70v/100v&amp;8Ω.</li> <li>Max SPL: 112±2dB.</li> <li>High sensitivity: 102±2dB.</li> <li>Equipped with brackets for installation.</li> <li>Outline dimension:285(W) × 205(H)× 280(L) mm.</li> </ul>	3900
47	DSP1650	<ul> <li>50W Horn Speaker Waterproof Speaker, made of High Quality ABS</li> <li>Waterproof: IP66.</li> <li>Rated power: 50W (6-12-25-50W-8Ω stepping).</li> <li>Input signal: 100v&amp;8Ω.</li> <li>Max SPL: 123±2dB.</li> <li>High sensitivity: 102±2dB.</li> <li>Equipped with brackets for installation.</li> <li>Outline dimension: 404(W) × 266(H)× 376(L) mm.</li> </ul>	5750

