



NO	Model	Description	Picture	Price
1	DM835	<ul> <li>20W Smart Home Stereo Music Amplifier 5 inputs</li> <li>Support: USB, Bluetooth, AUX, FM Radio, SD Card.</li> <li>Voltage input, AC 100-240V, 50/60Hz.</li> <li>Speaker output: Stereo output (4-16Ω).</li> <li>Stereo Built-in 20W (2x10W amplifier).</li> <li>With remote control operation.</li> <li>Touch button operation, visible LCD display.</li> <li>not equipped with in-wall plastic box.</li> </ul>	UNIVERSAL SERIAL BUS  ((((Q))))  FM  Bluetooth  SAUX INPUT	5200
2	M2W or M2U	<ul> <li>20W Smart Home Stereo Music Amplifier, 5 inputs+2 Ceiling Speakers</li> <li>Support: USB, Bluetooth, AUX IN, FM Radio, SD Card.</li> <li>Voltage input, AC 100-240V, 50/60Hz.</li> <li>Speaker output: Stereo output (4-16Ω).</li> <li>Stereo Built-in 20W (2x10W amplifier).</li> <li>With remote control operation&amp; in-wall plastic box.</li> <li>Touch button, visible LCD display.</li> </ul>	Bluetooth Sauxinput	6600
3	DSP602BT	<ul> <li>20W Bluetooth Stereo Music Ceiling Speakers with wide angle of proliferation, big output power</li> <li>2*10W/ 6.5" Bluetooth Ceiling Loudspeaker</li> <li>Bluetooth 4.0 wireless connection.</li> <li>With AUX Input .</li> <li>Built-in two-channel stereo amplifier in the Speakers</li> <li>Voltage input: AC 100-240V,50-60Hz.</li> <li>Speaker output: Stereo output (8Ω).</li> <li>Stereo/Mono Switch</li> <li>Volume control Knob in the Speaker.</li> </ul>	3Bluetooth SAUX INPUT	6500
4	DM837	20W Smart Android Touchscreen Stereo Home Music Amplifier 5 inputs  ■ 3.5"TFT Full Screen, visible LCD display.  ■ Support: USB, Bluetooth, AUX IN, FM Radio, SD Card.  ■ Speaker output: Stereo output (8Ω). ■ Voltage input, AC 100-240V, 50/60Hz.  ■ Stereo Built-in 20W (2x10W amplifier).  ■ With remote control operation& in-wall plastic box.  ■ Outline dimension: 86x86x38mm	Bluetooth  UNIVERSAL SERIAL BUS FM  SAUX INPUT	8400







5	DM836II	Network 40W Network Smart Touch Screen On-wall Stereo and Smart Home music Amplifier (8Ω)  • 5.0" TFT Full Screen, visible LCD display.  • Support LAN Network& Mobile App.  • Stereo 40W (2x20W) amplifier with (8Ω).  • Support: USB, Bluetooth, AUX, internet Radio, SD Card.  • With timing function and memory function • Speaker output: Stereo output (8Ω).  • Voltage input, AC 100-240V, 50/60Hz.  • Built-in Hi-Fi grade digital power amplifier.  • Outline dimension: 172x86x50mm.  • Net weight: 0.4kg.	Bluetooth SS SAUX INPUT  CInternet Radio	17600
6	DM838	<ul> <li>Wi-Fi 40W Network Smart Touch Screen</li> <li>On-wall Stereo and Home music Amplifier (8Ω)</li> <li>5.0"TFT Full Screen, visible LCD display.</li> <li>Support LAN &amp; Wi-Fi &amp; Mobile App, Airplay.</li> <li>Stereo 40W (2x20W) amplifier with (8Ω).</li> <li>Support: Bluetooth, AUX IN, SD Card, Internet Radio.</li> <li>With timing function and memory function</li> <li>Built-in Hi-Fi grade digital power amplifier</li> <li>Store Built in Music.</li> <li>Voltage input, AC 100-240V, 50/60Hz.</li> <li>Outline dimension: 172x86x50mm.</li> <li>Net weight: 0.4kg.</li> </ul>	Bluetooth SEX NPUT	18000







7	DM858	<ul> <li>Wi-Fi 80W Network Smart Touch Screen</li> <li>2 -Zone On-wall Stereo and Home music Amplifier (8Ω)</li> <li>7.0"TFT Full Screen, visible LCD display.</li> <li>Support 2-zone / 4ch independent control, volume. Independent adjustment.</li> <li>Stereo 80W (4x20W) amplifier with (8Ω).</li> <li>Support: Bluetooth, AUX IN, SD Card, Internet Radio.</li> <li>Built-in 10-band equalizer.</li> <li>Support LAN &amp; Wi-Fi &amp; Mobile App, Airplay.</li> <li>With timing function and memory function.</li> <li>Built-in Hi-Fi grade digital power amplifier.</li> <li>Wi-Fi Intercom Talk between the units.</li> <li>Voltage input, AC 100-240V, 50/60Hz.</li> <li>Outline dimension: 175x124x52mm</li> <li>Net weight: 0.7kg.</li> </ul>	Bluetooth  SAUX INPUT  INTERNET RADIO	Soon
8	MP135	35W multi-function Mini Mixer Amplifier 4 inputs wit USB, SD card, Bluetooth  Audio Source: 4 inputs (1Mic,1 AUX, USB player, Bluetooth)  Speaker Output: 100V & 8 ohms  With MIC priority function  MP3 player, Bluetooth  Freq. Response: 80-16kHz  LED indicators for power, clip, protect and signal.  Protection short-circuit, clip, overload and high temp  Support USB record function  Power supply: AC 110-240V  Outline dimension& weigh: 280x187x65mm, 1.8kg	1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	7800
9	WAT- 60ML watania	60 W (2x30W) Mini Stereo Amplifier ,USB, SD ,Bluetooth  Audio Input: 2 Mic,1 AUX ,USB, SD, Bluetooth & 1 Aux Out  Speaker Output: Stereo output (4-16 ohm)  Rated Power: 2x30W (stereo speaker output)  Remote control for easy operation  Freq. Response: 20Hz-22kHz  Support USB record function by mic or Aux input  LED display, digital volume control  Outline dimension& weight: 180×145×60mm & 0.8kg.	SE S	6300







10	Mini60	60 W (2x30W) Mini Stereo Amplifier ,USB, SD ,Bluetooth  Audio Input: 2 Mic,1 AUX ,USB, SD, Bluetooth & 1 Aux Out  Speaker Output: Stereo output (4-16 ohm)  Rated Power: 2x30W (stereo speaker output)  Remote control for easy operation  Freq. Response: 20Hz-22kHz  Support USB record function by MIC or Aux input  LED display, digital volume control  Outline dimension& weight: 180×145×60mm & 0.8kg.	* SIDSOPR	6600
11	Mini40BT	80W (2x40W) Stereo Amplifier ,USB, SD ,Bluetooth  Audio Input: 1 AUX ,USB, Bluetooth & 1 Aux Out  Speaker Output: Stereo output (8 ohm)  Rated Power: 2x40W (stereo speaker output)  Remote control for easy operation  Freq. Response: 20Hz-32kHz  LED display, digital volume control  Outline dimension: 138×136×55mm  weight:0.33kg.	INCIDENT Stores Shortesth USB Digital Angli Angli for Volume Committee Commi	6800
12	MP160	60W multi-function Mini Mixer Amplifier 4 inputs wit USB, SD card , Bluetooth  Audio Input: 4 inputs(1 Mic,1 AUX ,USB player, Bluetooth)  Speaker Output: 100V & 4 ohms  With MIC priority function  MP3 player, Bluetooth  Freq. Response: 80-16kHz  LED indicators for power, clip, protect and signal.  Protection short-circuit, clip, overload and high temp  Support USB record function  Power supply: AC 110-240V  Outline dimension: 280x187x65mm  Net weight: 1.8kg	From	8800







		60W Mini Digital Mixer Amplifier with USB, FM Radio,		
		•		
		Bluetooth&EMC Alarm Input For emergency Evacuation.		
		●Audio Input: 8 inputs (2 Mic, 2 AUX, 1Mic/AUX ,FM Radio		
		,EMC , USB MP3 player & Bluetooth) & 1 Aux Out		
		•Speaker Output: 70V/100V & 4 -16 ohms		
		Remote control for easy operation		
13	MP60UB	<ul><li>MP3 player, Bluetooth &amp; FM Radio with Antenna.</li></ul>	8888 : = ****	0000
13	IVIPOOOB	●EMC input For Emergency Evacuation in case of Alarm .		3000
		<ul> <li>Mic1 with priority function &amp;Mic2 with phantom power.</li> </ul>		
		●LED indicators for power.		
		<ul> <li>Protection short-circuits, clip, overload and heat.</li> </ul>		
		●Power supply: AC 110-240V & DC 24V		
		●Outline dimension: 247x198x66mm		
		■Net weight : 2.6kg.		
		60W 6 Zones Mixer Amplifier with 2 Mic&3 Line Input		
		Audio Input: 2 Mic , 3 AUX & 1 Aux Out		9000 Soon
		6 zones output, with individual zone switch		
		• 100Vspeaker output		Soon
		• 2 MIC, Mic 1 with priority and muting function		
		Each AUX &Mic input with individual volume control		
14	<b>MP260</b>	Bass & Treble tone control for sound quality	Will fill the frequency of the state of the	
		Mic 1 with priority muting function		
		Protection and alarm in case of output short-circuit.		
		Five-element LED level meter sound level		
		Remote control for easy operation		Soon
		●Outline dimension: 485×340×88mm		
		■Net Weight : 4.2kg.		
		120WMixer Amplifier with USB, FM Radio , BT&EMC Alarm		
		Input For emergency Evacuation.		
		•Audio Input: 8 inputs (2 Mic, 2 AUX, 1Mic/AUX ,FM	l ne	Soon
	NA/AT	Radio ,EMC , USB MP3 player & Bluetooth) & 1 Aux Out		
45	WAT-	•Speaker Output: 70V/100V & 4 -16 ohms		Soon
15	120BU	Remote control for easy operation		12900
	<u>watania</u>	<ul><li>MP3 player, Bluetooth &amp; FM Radio with Antenna.</li></ul>	8888 : = ****	
		●EMC input For Emergency Evacuation in case of Alarm .		
		Mic1 with priority function &Mic2 with phantom power.	THE MET METHERS AND SAME THIRD WESTER OF	
		•LED indicators for power.		







		Protection short-circuits, clip, overload and heat.		
		●Power supply: AC 110-240V & DC 24V		
		Outline dimension: 247x198x66mm		
		Net weight : 2.6kg		
		120WMixer Amplifier with USB, FM Radio , BT&EMC Alarm		
		Input For emergency Evacuation.		
		●Audio Input: 8 inputs (2 Mic, 2 AUX, 1Mic/AUX ,FM		
		Radio ,EMC , USB MP3 player & Bluetooth) & 1 Aux Out		
		●Speaker Output: 70V/100V & 4 -16 ohms		
		Remote control for easy operation		
16	MP120UB	●MP3 player, Bluetooth & FM Radio with Antenna.	8888	13500
		●EMC input For Emergency Evacuation in case of Alarm .		
		<ul><li>Mic1 with priority function &amp;Mic2 with phantom power.</li></ul>	ALC 10.000 10.000 10.000 10.000 10.000 10.000 10.000 10.000 10.000 10.000 10.000 10.000 10.000 10.000 10.000 1	
		●LED indicators for power.		
		<ul><li>Protection short-circuits, clip, overload and heat.</li></ul>		
		●Power supply: AC 110-240V & DC 24V		
		●Outline dimension: 247x198x66mm& Net weight : 2.6kg		
		120W Mixer Amplifier with USB, 4 Mic & 2 AUX		
		• Audio Input: 7 (4 MIC,2 AUX, 1 USB) & 1 Aux Out		
		• 100V Speaker output		
		5-unit LED display level indicators		
		Output short-circuit protection	** ****** ****** *********************	
17	MP120B	Individual volume control for each audio input	6 AAAAAAAA	SOON
		Mic 1 with priority muting function	to he he he he he he he .	
		Remote control for easy operation		
		Individual volume control for all inputs		
		• Outline dimension: 430×300×88mm		
		●Net weight : 7kg		







18	MP212U	<ul> <li>120W 6 Zones Mixer Amplifier BT/MP3/USB/SD &amp;FM Radio</li> <li>Audio Input: 2MIC, 1USB, 3AUX, BT,USB &amp;SD &amp; 1 Aux Out.</li> <li>Speaker Output: 6 channels @ 100V outputs.</li> <li>Mute function, easy to insert priority broadcast.</li> <li>Each zone with independent switch; bass and treble.</li> <li>5-unit LED display level indicators.</li> <li>Output short-circuit protection.</li> <li>Individual volume control for each audio input.</li> <li>Mic 1 with priority muting function.</li> <li>Remote control for easy operation.</li> <li>Outline dimension: 430×280×88mm.</li> </ul>	16650
		<ul> <li>Net weight: 8.9kg.</li> <li>120W6 Zones Mixer Amplifier with BT/USB/SD /FM</li> </ul>	
19	MP310U	<ul> <li>Audio Input: 4 MIC,3 AUX,1 USB, BT &amp;1 SD &amp;1 Aux Out</li> <li>6 zones speaker outputs with individual volume</li> <li>Control for each zone</li> <li>Speaker Output: 100V, 4-16 ohm</li> <li>Short-circuit protection, overload &amp; DC protection.</li> <li>With built-in chime.</li> <li>5-unit LED display level indicators</li> <li>Individual volume control for each audio input</li> <li>Mic 1 with priority muting function</li> <li>Remote control for easy operation</li> <li>Outline dimension: 418×355×88mm</li> <li>Net weight: 11.5kg.</li> </ul>	26600
20	MP250UB	250W Digital Mixer Amplifier with USB, FM Radio, BT &EMC Alarm Input For Emergency Evacuation.  • Audio Input: 9 inputs (2 Mic, 2 AUX, 1Mic/AUX, 2 EMC, FM Radio, USB MP3 player &Bluetooth) &1 Aux Out  • Speaker Output: 70V/100V & 4 -16 ohms.  • Remote control for easy operation.  • MP3 player, Bluetooth & FM Radio with Antenna.  • EMC input For Emergency Evacuation in case of Alarm.  • Mic1 with priority function &Mic2 with phantom power.  • LED indicators for power.  • Protection short-circuits, clip, overload and heat.  • Power supply: AC 110-240V.	18000







Mic 1 with priority and muting function  5-unit LED display level indicators Individual volume control for each audio input  Remote control for easy operation  Outline dimension: 485×400×88mm&  Net weight: 10.3kg  250W Mixer Amplifier with 3 Mic & 2 AUX IN , 1 AUX Out.  Mic 1 with priority and muting function.  Speaker Output: 70V/100V & 4 -16 ohms  Individual volume control for each microphone &line  Bass and treble control.  Individual volume control for each audio input  Outline dimension: 418×338×88mm  Net weight: 10.3kg.  250W 2 Zones , Remote paging Mixer Amplifier with  Bluetooth, USB &FM Radio &F ire Alarm Trigger.  Audio Input: 4 MIC,2 AUX ,1 USB &1 Aux Out  Speaker Output: 100V.  Chime/Siren/Mute dry contact with gain control.  Speaker Output: 70V/100V & 4 -16 ohms  Individual volume control for each audio input  Support 2 remote paging stations.		و انتظمه امتیا	DOTTA Addition Title List 100	<u> </u>	
Audio Input: 2 MIC, 3 AUX, 1 USB & 1 SD &1 Aux Out 6 zones speaker outputs with individual On/Off Control for each zone Speaker Output:100V. Short-circuit, overload and high temp protection. Mic 1 with priority and muting function S-outlice dimension: 485×400×88mm& Net weight: 10.3kg  MP600PIII  MP600PIII  MP600PIII  MP600U  MP600U  MP600U  With Fire Alarm Connection  Audio Input: 4 MIC, 2 AUX, 1 USB & 1 Aux Out Speaker Output: 100V. Speaker Output: 70V/100V & 4 -16 ohms Individual volume control for each audio input Speaker Output: 100V. Speaker Output: 100V. Speaker Output: 100V. Speaker Output: 70V/100V & 4 -16 ohms Individual volume control for each audio input Support 2 remote paging stations.			-		
Control for each zone Speaker Output: 100V. Short-circuit, overload and high temp protection. Mic 1 with priority and mutting function Outline dimension: 485×400×88mm& Net weight: 10.3kg  250W Mixer Amplifier with 3 Mic & 2 AUX IN , 1 AUX Out. Mic 1 with priority and muting function. Speaker Output: 70V/100V & 4 -16 ohms Individual volume control for each audio input Outline dimension: 418×338×88mm Net weight: 10.3kg.  MP600PIII  MP600PIII  MP600U  with Fire Alarm Connection  With Fire Alarm Connection Speaker Output: 100V. Chime/Siren/Mute dry contact with gain control. Speaker Output: 100V. Speaker Output: 70V/100V & 4 -16 ohms Support 2 remote paging stations.			· · · · · · · · · · · · · · · · · · ·		
MP225U  MP225U  Speaker Output: 100V. Short-circuit, overload and high temp protection. Mic 1 with priority and muting function S-unit LED display level indicators Individual volume control for each audio input Remote control for easy operation Outline dimension: 485×400×88mm& Net weight: 10.3kg  250W Mixer Amplifier with 3 Mic & 2 AUX IN , 1 AUX Out. Mic 1 with priority and muting function. Speaker Output: 70V/100V & 4 -16 ohms Individual volume control for each audio input Outline dimension: 418×338×88mm Net weight: 10.3kg.  MP600U  MP600U  MP600U  With Fire Alarm Connection  with Fire Alarm Connection  With Fire Alarm Connection  Speaker Output: 70V/100V & 4 -16 ohms Individual volume control for each audio input Speaker Output: 100V. Chime/Siren/Nute dry contact with gain control. Speaker Output: 70V/100V & 4 -16 ohms Individual volume control for each audio input Support 2 remote paging stations.			· · · · · · · · · · · · · · · · · · ·		22500
### Short-circuit, overload and high temp protection.    Mic 1 with priority and muting function					
MP2250  Mic 1 with priority and muting function 5-unit LED display level indicators Individual volume control for each audio input Remote control for easy operation Outline dimension: 485×400×88mm& Net weight: 10.3kg  250W Mixer Amplifier with 3 Mic & 2 AUX IN , 1 AUX Out. Mic 1 with priority and muting function. Speaker Output: 70V/100V & 4-16 ohms Individual volume control for each audio input Outline dimension: 418×338×88mm Net weight: 10.3kg.  250W 2 Zones , Remote paging Mixer Amplifier with Bluetooth, USB &FM Radio &F ire Alarm Trigger. Audio Input: 4 MIC,2 AUX ,1 USB &1 Aux Out Speaker Output: 100V. Chime/Siren/Mute dry contact with gain control. Speaker Output: 70V/100V & 4-16 ohms Individual volume control for each audio input Speaker Output: 100V. Chime/Siren/Mute dry contact with gain control. Speaker Output: 70V/100V & 4-16 ohms Individual volume control for each audio input Support 2 remote paging stations.					
S-unit LED display level indicators     Individual volume control for each audio input     Remote control for easy operation     Outline dimension: 485×400×88mm&     Net weight: 10.3kg      250W Mixer Amplifier with 3 Mic & 2 AUX IN , 1 AUX Out.     Mic 1 with priority and muting function.     Speaker Output: 70V/100V & 4 -16 ohms     Individual volume control for each microphone &line     Bass and treble control.     Individual volume control for each audio input     Outline dimension: 418×338×88mm     Net weight: 10.3kg.      250W 2 Zones , Remote paging Mixer Amplifier with     Bluetooth, USB &FM Radio &F ire Alarm Trigger.     Audio Input: 4 MIC, 2 AUX , 1 USB &1 Aux Out     Speaker Output: 100V.     Chime/Siren/Mute dry contact with gain control.     Speaker Output: 70V/100V & 4 -16 ohms     Individual volume control for each audio input     Support 2 remote paging stations.	21	MP225U	· · · · · · · · · · · · · · · · · · ·		
<ul> <li>Individual volume control for each audio input</li> <li>Remote control for easy operation</li> <li>Outline dimension: 485×400×88mm&amp;</li> <li>Net weight: 10.3kg</li> <li>250W Mixer Amplifier with 3 Mic &amp; 2 AUX IN, 1 AUX Out.</li> <li>Mic 1 with priority and muting function.</li> <li>Speaker Output: 70V/100V &amp; 4 -16 ohms</li> <li>Individual volume control for each microphone &amp;line.</li> <li>Bass and treble control.</li> <li>Individual volume control for each audio input</li> <li>Outline dimension: 418×338×88mm</li> <li>Net weight: 10.3kg.</li> <li>250W 2 Zones, Remote paging Mixer Amplifier with Bluetooth, USB &amp;FM Radio &amp;F ire Alarm Trigger.</li> <li>Audio Input: 4 MIC,2 AUX, 1 USB &amp;1 Aux Out</li> <li>Speaker Output: 100V.</li> <li>Chime/Siren/Mute dry contact with gain control.</li> <li>Speaker Output: 70V/100V &amp; 4 -16 ohms</li> <li>Individual volume control for each audio input</li> <li>Speaker Output: 70V/100V &amp; 4 -16 ohms</li> <li>Individual volume control for each audio input</li> <li>Support 2 remote paging stations.</li> </ul>	21		, , ,	Waterway	
Remote control for easy operation Outline dimension: 485×400×88mm& Net weight: 10.3kg  250W Mixer Amplifier with 3 Mic & 2 AUX IN , 1 AUX Out. Mic 1 with priority and muting function. Speaker Output: 70V/100V & 4 -16 ohms Individual volume control for each microphone &line Bass and treble control. Individual volume control for each audio input Outline dimension: 418×338×88mm Net weight: 10.3kg.  250W 2 Zones , Remote paging Mixer Amplifier with Bluetooth, USB &FM Radio &F ire Alarm Trigger. Audio Input: 4 MIC,2 AUX ,1 USB &1 Aux Out Speaker Output: 100V. Chime/Siren/Mute dry contact with gain control. Speaker Output: 70V/100V & 4 -16 ohms Individual volume control for each audio input Support 2 remote paging stations.			· ·	1111111 2 2 2 2 2 2 2 2 2 2	
Outline dimension: 485×400×88mm& Net weight: 10.3kg  250W Mixer Amplifier with 3 Mic & 2 AUX IN , 1 AUX Out. Mic 1 with priority and muting function. Speaker Output: 70V/100V & 4 -16 ohms Individual volume control for each microphone &line Bass and treble control. Individual volume control for each audio input Outline dimension: 418×338×88mm Net weight: 10.3kg.  250W 2 Zones , Remote paging Mixer Amplifier with Bluetooth, USB &FM Radio &F ire Alarm Trigger. Audio Input: 4 MIC,2 AUX ,1 USB &1 Aux Out Speaker Output: 100V. Chime/Siren/Mute dry contact with gain control. Speaker Output: 70V/100V & 4 -16 ohms Individual volume control for each audio input Support 2 remote paging stations.			•		
Net weight: 10.3kg  250W Mixer Amplifier with 3 Mic & 2 AUX IN , 1 AUX Out.  Mic 1 with priority and muting function.  Speaker Output: 70V/100V & 4 -16 ohms  Individual volume control for each microphone &line  Bass and treble control.  Individual volume control for each audio input  Outline dimension: 418×338×88mm  Net weight: 10.3kg.  250W 2 Zones , Remote paging Mixer Amplifier with Bluetooth, USB &FM Radio &F ire Alarm Trigger.  Audio Input: 4 MIC,2 AUX ,1 USB &1 Aux Out  Speaker Output: 100V.  Chime/Siren/Mute dry contact with gain control.  Speaker Output: 70V/100V & 4 -16 ohms Individual volume control for each audio input  Support 2 remote paging stations.			· ·		
22 MP600PIII  MP600PIII  MP600PIII  Individual volume control for each microphone &line  Bass and treble control.  Individual volume control for each audio input  Outline dimension: 418×338×88mm  Net weight: 10.3kg.  250W 2 Zones, Remote paging Mixer Amplifier with Bluetooth, USB &FM Radio &F ire Alarm Trigger.  Audio Input: 4 MIC,2 AUX,1 USB &1 Aux Out  Speaker Output: 100V.  Chime/Siren/Mute dry contact with gain control.  Speaker Output: 70V/100V & 4 -16 ohms Individual volume control for each audio input  Support 2 remote paging stations.					
MP600PIII  • Mic 1 with priority and muting function. • Speaker Output: 70V/100V & 4 -16 ohms • Individual volume control for each microphone &line • Bass and treble control. • Individual volume control for each audio input • Outline dimension: 418×338×88mm • Net weight: 10.3kg.  250W 2 Zones , Remote paging Mixer Amplifier with Bluetooth, USB &FM Radio &F ire Alarm Trigger. • Audio Input: 4 MIC,2 AUX ,1 USB &1 Aux Out • Speaker Output: 100V. • Chime/Siren/Mute dry contact with gain control. • Speaker Output: 70V/100V & 4 -16 ohms • Individual volume control for each audio input • Support 2 remote paging stations.			<u> </u>		
Speaker Output: 70V/100V & 4 -16 ohms Individual volume control for each microphone &line Bass and treble control. Individual volume control for each audio input Outline dimension: 418×338×88mm Net weight: 10.3kg.  250W 2 Zones, Remote paging Mixer Amplifier with Bluetooth, USB &FM Radio &F ire Alarm Trigger. Audio Input: 4 MIC,2 AUX,1 USB &1 Aux Out Speaker Output: 100V. Chime/Siren/Mute dry contact with gain control. Speaker Output: 70V/100V & 4 -16 ohms Individual volume control for each audio input Support 2 remote paging stations.			· ·		new
Bass and treble control. Individual volume control for each audio input Outline dimension: 418×338×88mm Net weight: 10.3kg.  250W 2 Zones, Remote paging Mixer Amplifier with Bluetooth, USB &FM Radio &F ire Alarm Trigger. Audio Input: 4 MIC,2 AUX,1 USB &1 Aux Out Speaker Output: 100V. Chime/Siren/Mute dry contact with gain control. Speaker Output: 70V/100V & 4-16 ohms Individual volume control for each audio input Support 2 remote paging stations.			• Speaker Output: 70V/100V & 4 -16 ohms		
<ul> <li>Bass and treble control.</li> <li>Individual volume control for each audio input</li> <li>Outline dimension: 418×338×88mm</li> <li>Net weight: 10.3kg.</li> <li>250W 2 Zones, Remote paging Mixer Amplifier with Bluetooth, USB &amp;FM Radio &amp;F ire Alarm Trigger.</li> <li>Audio Input: 4 MIC,2 AUX, 1 USB &amp;1 Aux Out</li> <li>Speaker Output: 100V.</li> <li>Chime/Siren/Mute dry contact with gain control.</li> <li>Speaker Output: 70V/100V &amp; 4 -16 ohms</li> <li>Individual volume control for each audio input</li> <li>Support 2 remote paging stations.</li> </ul>	22	MDCOODIII	•Individual volume control for each microphone &line	TITI BOODER WARRENCO THE	
Outline dimension: 418×338×88mm  Net weight: 10.3kg.  250W 2 Zones, Remote paging Mixer Amplifier with Bluetooth, USB &FM Radio &F ire Alarm Trigger.  Audio Input: 4 MIC,2 AUX,1 USB &1 Aux Out Speaker Output: 100V.  Chime/Siren/Mute dry contact with gain control. Speaker Output: 70V/100V & 4-16 ohms Individual volume control for each audio input Support 2 remote paging stations.	22	IVIPOUPIII	Bass and treble control.	De l'Industrial de l'Arriva Maria Maria Auria Au	
<ul> <li>Net weight: 10.3kg.</li> <li>250W 2 Zones, Remote paging Mixer Amplifier with Bluetooth, USB &amp;FM Radio &amp;F ire Alarm Trigger.</li> <li>Audio Input: 4 MIC,2 AUX,1 USB &amp;1 Aux Out</li> <li>Speaker Output: 100V.</li> <li>Chime/Siren/Mute dry contact with gain control.</li> <li>Speaker Output: 70V/100V &amp; 4 -16 ohms</li> <li>Individual volume control for each audio input</li> <li>Support 2 remote paging stations.</li> </ul>			Individual volume control for each audio input		
MP600U  With Fire Alarm Connection  MP600U  250W 2 Zones, Remote paging Mixer Amplifier with Bluetooth, USB &FM Radio &F ire Alarm Trigger.  Audio Input: 4 MIC,2 AUX,1 USB &1 Aux Out  Speaker Output: 100V.  Chime/Siren/Mute dry contact with gain control.  Speaker Output: 70V/100V & 4 -16 ohms  Individual volume control for each audio input  Support 2 remote paging stations.			Outline dimension: 418×338×88mm		
MP600U  With Fire Alarm Connection  Bluetooth, USB &FM Radio &F ire Alarm Trigger.  • Audio Input: 4 MIC,2 AUX,1 USB &1 Aux Out • Speaker Output: 100V. • Chime/Siren/Mute dry contact with gain control. • Speaker Output: 70V/100V & 4 -16 ohms • Individual volume control for each audio input • Support 2 remote paging stations.			Net weight : 10.3kg.		
<ul> <li>Audio Input: 4 MIC,2 AUX,1 USB &amp;1 Aux Out         <ul> <li>Speaker Output: 100V.</li> <li>Chime/Siren/Mute dry contact with gain control.</li> <li>Speaker Output: 70V/100V &amp; 4 -16 ohms</li></ul></li></ul>					
MP600U  with Fire Alarm Connection  Alarm Connection  Addio Input: 4 Mic,2 AOX,1 USB &1 AUX OUT  Speaker Output: 100V.  Chime/Siren/Mute dry contact with gain control.  Speaker Output: 70V/100V & 4 -16 ohms  Individual volume control for each audio input  Support 2 remote paging stations.					new
<ul> <li>With Fire Alarm Connection</li> <li>Speaker Output: 70V/100V &amp; 4 -16 ohms</li> <li>Individual volume control for each audio input</li> <li>Support 2 remote paging stations.</li> </ul>		MP600U			new
Speaker Output: 70V/100V & 4 -16 ohms  Individual volume control for each audio input  Support 2 remote paging stations.			i i		
• Individual volume control for each audio input • Support 2 remote paging stations.  • Support 2 remote paging stations.	23	with Fire	•		33000
•Support 2 remote paging stations.		Alarm		AD IN M   COMM REMORE	
		Connection	· ·		
▼IVIIC Z → WILLI PHANTONI POWCI → OV ANA SAIN CONTINU			Mic 2-4 with phantom power 48V and gain control		
Outline dimension& Net weight:418×338×88mm& 10.3kg.			, ,		







24	MA2250  2CH  Mosque  Amplifier  With Echo	2*250W Mixer Amplifier, 2CH, with USB, BT, Echo.  • Audio Input: 3 MIC,1 AUX,1 USB &1 Aux Out • Speaker Output: 70V/100V & 4-16 ohms. • 2-reverb Volume control for CH1, CH2. • Two individual channel output CH1, CH2. • Master volume for each CH. • Adjustable volume for each MIC. • Individual bass and treble for each CH. • Each microphone has 48V phantom power • With warning tone function.	AND THE PARTY OF T	32250
		<ul> <li>Automatic two-speed temperature control fan.</li> <li>Outline dimension&amp; Net weight: 484×412×90mm&amp;16kg.</li> </ul>		
25	MP610U	<ul> <li>Source of Source of Superson of S</li></ul>		32200
26	MP1010U	350W 6 Zones Mixer Amplifier with BT/USB/SD /FM  Audio Input: 4 MIC,3 AUX,1 USB, BT &1 SD&1 Aux Out  6 zones speaker outputs with individual volume Control for each zone  Speaker Output: 100V, 4-16 ohm  Short-circuit protection, overload & DC protection.  with built-in chime  5-unit LED display level indicators  Individual volume control for each audio input  Mic 1 with priority muting function  Remote control for easy operation  Outline dimension: 418×355×88mm  Net weight: 16kg		35000







CONCE DITA Addition Title List TOD ZOZA TI					
		350W 6 Zones, Remote paging Mixer Amplifier with BT, USB			
		, FM Radio & EMC Fire Alarm Trigger	l no	ew	
	MP6350U	Audio Input: 4 MIC,2 AUX ,1 USB &1 Aux Out	W W	40600 42500 51800	
		Chime/Siren/Mute dry contact with gain control			
	Fire Alarm	• Speaker Output: 70V/100V & 4 -16 ohms	We Can't Stepans		
27	Connection	•independent volume adjustment knob of six zones		40600	
	&	•Support remote paging stationswith zone control 6 zone			
	Remote	Support 2-channelremote paging.	CC A TO COMPANY TO THE PARTY OF		
	paging	●Mic 2-4 with phantom power 48V and gain control			
	Page 8	•Individual volume control for each audio input			
		Outline dimension430×390×88mm			
		Net weight : 10.2kg.			
		450W 6 zones Mixer amplifier with Bluetooth/FM/USB/SD			
		• Audio Input: 2 MIC,3 AUX ,1 USB &1 SD&1 Aux Out			
		• 6 zones speaker outputs with individual On/Off			
		Control for each zone			
		Speaker Output: 100V		40600 42500	
28	MP245U	<ul> <li>Short-circuit, overload and high temp protection.</li> </ul>	TOTAL MODERN	42500	
20	WIP243U	Mic 1 with priority and muting function		42300	
		5-unit LED display level indicators			
		<ul> <li>Individual volume control for each audio input</li> </ul>			
		Remote control for easy operation			
		Outline dimension: 485×400×88mm			
		Net weight : 12.8kg			
		500W 6 Zones, Remote paging Mixer Amplifier with BT, USB			
		, FM Radio & EMC Fire Alarm Trigger			
		<ul> <li>Audio Input: 4 MIC,2 AUX ,1 USB &amp;1 Aux Out</li> </ul>	l n	ew)	
	MP6500U	Built in two zones 100V output		40600 42500	
		Chime/Siren/Mute dry contact with gain control			
	Fire Alarm	• Speaker Output: <b>70V/100V &amp; 4 -16 ohms</b>	-0.0.0		
29	Connection	•independent volume adjustment knob of six zones	00000000000000000000000000000000000	51800	
	&	•Support RJ-45 remote paging stations, 2-channel.	CE EPC UNITED MARIE A		
	Remote	Mic 2-4 with phantom power 48V and gain control	( )		
	paging	Individual volume control for each audio input			
		Outline dimension: 430×390×88mm			
		Net weight : 11.3kg.			
		- Het Weight Lindag.			







30	MP265U	<ul> <li>650W 6 zones Mixer amplifier with Bluetooth/FM/USB/SD</li> <li>Audio Input: 2 MIC,3 AUX ,1 USB &amp;1 SD&amp;1 Aux Out.</li> <li>6 zones speaker outputs with individual On/Off . Control for each zone .</li> <li>Speaker Output: 100V .</li> <li>Short-circuit, overload and high temp protection.</li> <li>Mic 1 with priority and muting function.</li> <li>5-unit LED display level indicators.</li> <li>Individual volume control for each audio input.</li> <li>Remote control for easy operation.</li> <li>Outline dimension: 485×400×88mm.</li> <li>Net weight: 12.8kg.</li> </ul>	Watchestown real formation of the first of t	49900
31	MP2765	650W 6 Zones 4.3" TFT Touch Screen Mixer Amplifier with Bluetooth, Timer, USB, SD &FM Radio  • Audio Input: 3 MIC,1 AUX,1 USB &1 SD&1 Aux Out  • 6 zones speaker outputs with individual On/Off Control for each zone  • Speaker Output: 100V  • 4.3" TFT touch screen& built-in chime  • Built-in 4giga MP3 program memory.  • AC Fuse, overload & DC protection.  • 5-unit LED display level indicators  • Mic 1 with priority muting function  • Individual volume control for each audio input  • Outline dimension: 418×338×88mm  • Net weight: 15kg.	WIN file replies to the replies to t	50000
32	MP906 Matrix & Mixer &Remote Paging	240W, 4x4 Matrix & Mixer Amplifier with Remote Paging  With USB/MP3, Bluetooth, Emergency Alarm  Built-in 4 separate amplifier, each channel RMS 60W  Speaker Output: 70/100V  5 AUX line input & 1 AUX line output  3 balanced Mic input with phantom power supply  4 remote paging stations, support cascaded linkage  Each AUX and Mic input with volume and Bass & Treble  Each channel can play different audio source  Support TEL input, built-in chime  Outline dimension& Weight: 485×340×215mm&28kg		80000







		490M Av4 Matrix & Miyor Amplifior with Domata Daging		
33	MP912 Matrix & Mixer &Remote Paging	<ul> <li>480W, 4x4 Matrix &amp; Mixer Amplifier with Remote Paging</li> <li>With USB/MP3, Bluetooth, Emergency Alarm</li> <li>Built-in 4 separate amplifier, each channel RMS 120W</li> <li>Speaker Output: 70/100V</li> <li>5 AUX line input &amp; 1 AUX line output</li> <li>3 balanced Mic input with phantom power supply</li> <li>4 remote paging stations, support cascaded linkage</li> <li>Each AUX and Mic input with volume and Bass &amp; Treble</li> <li>Each channel can play different audio source</li> <li>Support TEL input, built-in chime</li> <li>Outline dimension&amp; Weight: 485×340×215mm&amp; 30Kg.</li> </ul>		82000
34	MAG808 8x8 Digital Audio Matrix	<ul> <li>8x8 Digital Audio Matrix PA System, for multi-zone paging and multi-sources selection.</li> <li>7" Touch screen, built-in control software</li> <li>integrated with audio matrix, zones, timing, voice alarm</li> <li>8 channel balanced audio inputs, 8 channel balanced audio outputs</li> <li>each channel with individual EQ control</li> <li>Each zone support remote panel control, audio selection, audio input and volume control</li> <li>Support 4 remote paging microphone,</li> <li>Support 2 local Mic with phantom power supply</li> <li>Support MP3 playing (built-in audio or external USB), FM.</li> <li>Built-in 4G memory sticker, can extend to 32G</li> </ul>	• 5 5 5 5 <b>2111111</b> 5 5 5 5 5 5 • • • • • • • • • • • • •	CALL
35	MAG808R 8 Zones Remote Paging Mic	<ul> <li>8 Zones Remote Paging Microphone (Use with Matrix),</li> <li>Support 8 zones</li> <li>Clear signal level indication</li> <li>Built-in 2 kinds of chime signal</li> <li>Adjustable volume of MIC and chime</li> <li>Adopts D626 goose-neck microphone</li> <li>Adopts RJ45 interface for MIC connection, support the cascade linkage</li> </ul>		CALL







36	PAVA8500 8 Zone Voice Evacuatio n System	8 Zones – 500W - Voice Evacuation System, EN54-16  • 8 zones speaker output (extended up to 1000 zones)  • Built in 500W digital amplifier, integrated Dante technology  • One button alarm, built in EVAC message & Chime  • Support line detection of speakers (heavy load or short circuit or open circuit)  • 8 Zones speaker output with individual volume control  • Support remote Mic zones or group paging  • DC battery backup monitoring  • Real time monitor with EMC microphone for emergency evacuation  • 8 dry contact trigger input/output  • DC24V override output  • Support 100V Speaker  • Support PC control and buillt-in timer  • Comply with EN54-16 requirements	National Action and Ac	CALL
37	PAVA8500 E 8 Zone Voice Evacuatio n Extender	<ul> <li>8 Zones – 500W - Voice Evacuation Extender, EN54-16</li> <li>Built-in 500W digital amplifier, Dante technology</li> <li>8 zones speaker output with individual management</li> <li>Auto detection for system failure, AC/DC, paging Mic,</li> <li>Zones extendable by another extender amplifier</li> <li>Support remote control via computer</li> <li>Comply with EN54-16 requirements</li> </ul>	### ##################################	CALL
38	PAVA8008	Voice Evacuation Remote Paging Station  ■ Remote paging mic of PAVA8500  ■ has 16 zones capacity  ■ Zones extendable by extender Mic PAVA8008E  ■ System indicators of AC/DC, fault, Mic, etc.  ■ Comply with EN54-16 requirements		CALL
39	MP9807C	<ul> <li>DVD/CD/USB/MP3/MP4/VCD Player— Rack Mount</li> <li>Remote control &amp; USB</li> <li>LCD display screens to display CD/MP3/MP4</li> <li>Can select any song or any paragraph for play.</li> <li>Can Repeat any song or folder or any paragraph.</li> <li>L/R Stereo output 1 &amp;2 .</li> <li>Outline dimension:</li> <li>Outline dimension&amp; Weight: 484×365×88mm &amp;6.9kg.</li> </ul>	BOARD STATE OF THE	17590







40	MAG2107 C	Multi-channel Media Player – Rack Mount CD/USB/B.T/AM/FM & SD card  • Support Bluetooth/CD/USB/SD card  • Microcomputer control with light touch button  • FM/AM radio can store 40 stations respectively  • Stereo radio L/R output  • Stereo CD/MP3 L/R output  • Stereo Bluetooth L/R output  • Outline dimension& Weight: 483×210×44 mm&3.65kg.		24500
41	DW01	<ul> <li>Wi-Fi Audio Streaming With Bluetooth, USB, Line in.</li> <li>Support streaming source from online services, smart device memory, USB pen drive, NAS, Bluetooth and line in.</li> <li>Support Airplay, Spotify, Qplay, Deezer, QQMusic</li> <li>4-stream Mobile app.</li> <li>Bluetooth5.0 distance up to 30 meters</li> <li>Multiroom and multizone streaming</li> </ul>	ASSET USE SELECT SECTION	8500
42	MP9815E	Prerecorded Message For Emergency & Fire Alarm  • Automatic <u>and</u> Manual PLAY Message in case of Fire Alarm  • Prerecording message available from Mic or Line input.  • Serine and Alarm output.  • 1 minutes digital REC / PLAY message.  • Record and Output Volume Level control.	Forques fred WHINE  THE	25670







# <u>DSPPA-Audio Price List – Feb 2024 – P1</u> <u>AudioMixer</u>

41	ABK	High Quality 8 Channel Mixer	
	MC-8FX	S channel input audio mixer	
		●Up to 8 Mic input of XLR /6.3 mm	new
		• 1 groups of AUX output	ି ଚିତ୍ରି ବିଜ୍ନ ବ୍ୟୁ ସେବର ବ୍ୟୁ ବିଜ୍ନ ବ୍ୟୁ ବ୍ୟୁ ବ୍ୟୁ ବ୍ୟୁ ବ୍ୟୁ ବ୍ୟୁ ବ୍ୟୁ ବ୍ୟୁ
		Solo and Mute for each Channel	
		•99 kinds of delay effect processor (99DSP)	
		9-Band Main Equalizer	14750
		•3-Band Equalizer for Each Ch.	· Sadadadadadadadadadada - Idadadad.
		Mute Switch for Each Ch.	
		With Recording and built-in Bluetooth	
		MP3 player with USB input & SD card slot	
		•Support +48V Phantom power supply voltage	
		●With LCD & 2 Fan Cooling – 220VAC	
42	ABK	High Quality 12 Channel Mixer	
	MC-12FX	●12 channel input audio mixer	new
		●Up to 12 Mic input of XLR /6.3 mm	
		• 1 groups of AUX output	- GOOGOOO : : 200 0 0 0 0 0 0 0
		Solo and Mute for each Channel	
		•99 kinds of delay effect processor (99DSP)	
		●9-Band Main Equalizer	16850
		•3-Band Equalizer for Each Ch.	
		Mute Switch for Each Ch.	· . Dadadadadadadadadadada . Idadadada.
		With Recording and built-in Bluetooth	THE PARTY OF THE P
		MP3 player with USB input & SD card slot	
		•Support +48V Phantom power supply voltage	
		●With LCD & 2 Fan Cooling – 220VAC	







43	ABK	High Quality Mixer8 Channel, with Double Effect F1&F2		
	PMA-	•8 channel input audio mixer		DOW
	802FX	●Up to 8 Mic input of XLR /6.3 mm		new
	<b>Dual Echo</b>	• 1 Groups of AUX output		
	F1&F2	Solo and Mute for each Channel		
		With Double Effect 99DSP.	0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	14260
		●7-band EQ with can be adjusted from 140Hz to 3 KHz		14200
		Mute Switch for Each Ch.	0 0 0 0 0 0 0 0 0 MANN 000	
		With Recording and built-in Bluetooth		
		MP3 player with USB input & SD card slot		
		●Support +48V Phantom power supply voltage		
		●With LCD & 2 Fan Cooling – 220VAC.		
44	ABK	High Quality Mixer12 Channel, with Double Effect F1&F2		
	PMA-	●12 channel input audio mixer	0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	
	1202FX	●Up to12 Mic input of XLR /6.3 mm		new
	<b>Dual Echo</b>	• 1 Groups of AUX output		
	<u>F1&amp;F2</u>	Solo and Mute for each Channel		
		With Double Effect 99DSP.	កកកកកកកកកកកកកកកកកកកកកកកកកកកកកកកកកកកកក	17700
		●7-band EQ with can be adjusted from 140Hz to 3 KHz		17700
		With Recording and built-in Bluetooth		
		MP3 player with USB input & SD card slot		
		●Support +48V Phantom power supply voltage		
		●With LCD & 2 Fan Cooling – 220VAC		

