



<u>DSPPA-Audio Price List – Feb 2024 – P1</u> <u>Paging Microphones</u>

			,	
1	DM30	Desktop Dynamic Microphone		
		Anti - electromagnetic interference and anti-mobile phone		
		interference		3900
		With switch impact eliminated		
		 special technology eliminating noise when switching 	COSS S	
		on/off and it also avoids damage to the microphone		
		Desktop Condenser Microphone (Speech Range 10-30cm)		
2	CM30	Anti electromagnetic and mobile phone interference		
		With switch impact eliminated		4000
		 eliminating noise when switching on/off the microphone)	4800
		and also avoids microphone damage		
		•Support phantom power supply only		
		Desktop Condenser Microphone (Speech Range 10-60cm)	/	
3	CM62	Plug & play, easy to use.		5500
		Wide frequency response: 80-3000Hz		
		$ullet$ Output impedance \leq 200 Ω		
		•2 kinds power, DC3V or 48V phantom power	Base front Base back	
4	CM10	Dingdong Desktop Microphone with 2 Chimes		
		With built-in Chime		
		Adjustable chime volume.	1	0=00
		Easy to use, suitable for different occasions		9500
		Output voltage selectable.	R. R. S. S.	
		•Turn on & off chime function.		
		2 Zones Remote Paging Microphone		
	RM20	RJ-45 interface for power & signal		
		•support cascaded linkage		
5	used with	Built-in chime		11590
	MP600U	•special one-touch-to-talk		
		with two switches to control paging.		1
	DMA20	6 Zones Remote Paging Microphone		
	DIVIAZU	RJ-45 interface for power & signal		
	used with	•support cascaded linkage		
6		Built-in chime		18000
6	MP6500U			18000
	MDC2FOLL	•special one-touch-to-talk		
	MP6350U	•with two switches to control paging.		

Note: All Prices Not Including VAT





DSPPA-Audio Price List – Feb 2024 – P1

		6 Zanas Damata Daging Misyanhana		
7	CM12 used with MP825 - MP835 - MP906 - MP912	6 Zones Remote Paging Microphone		
		(working with MP825 , MP835 , MP906 & MP906 only)		15200
		Level indication		
		●Up to 6Zone control		
		Two built-in bell signals		15200
		Adjustable volume of microphone and bell		
		RJ45 socket connection.		
		Support cascading connection		
8		Duplex intercom system (Wired) Ideal for the bank,		5500
		securities, hospital, bus station etc. where guard glass		
		again theft is installed.		
	D850	High quality speaker & microphone		
		Adjustable volume with separate switch.		
		 Auto 2-way connect without pressing any button. 		
		•Anti-interference and noise-free function.		
	ABK KU-65-1	UHF 2 Microphone Wireless (2 Hand)	The last of the la	8000
		UHF Fixed Frequency Microphone System		
		LCD display (display channels and battery power)		
9		•working frequency 610-659.75MHz		
		Working distance About 60 meters		
		•Frequency and channel locked to protect anti-jamming.		
		UHF 2 Microphone Wireless (1 Hand + 1 Head or Clip)	1	
	ABK KU-65-2	UHF Fixed Frequency Microphone System		8000
		LCD display (display channels and battery power)		
10				
		working frequency 610-659.75MHz Washing distances About 60 maters		
		Working distance About 60 meters		
		•Frequency and channel locked to protect anti-jamming.		
11		Microphone Wireless (1 Hand or 1 Head+ Receiver)		
	DSP6710	With Rechargeable lithium battery.		
	or	•Stylish and simple appearance design.		
	DSP2020	working frequency: 1 GHz.		7000
	Α	Working distance About 30meters.	O - G-04	
		●Frequency response 20Hz~16KHz (±3dB).		
	l .	1 1 1 - 1 1	1	

Note: All Prices Not Including VAT





DSPPA-Audio Price List – Feb 2024 – P1

12	ABK SR-66A	High Range -2 Microphone Wireless (2 hand-held) Microphone UHF True Diversity Frequency Adjustable • Working distance :up to250 meters • LCD display (display group, channels and battery power) • 200 working frequency Quantity • Frequency range : 640-690MHz • S/N Ratio :105db • Power : Microphone 2*1.5v AA Batteries ,up to 15 hours		16200
13	DSPPA D5821 & D5811	True Diversity UHF Wireless Microphone System (2 handheld mic) •Working distance: up to250 meters • UHF200 channel PLL digital lock automatic communication function. • Adopt IR frequency pairing. • With display screen (to display frequency, channel, squelch, level, etc.). • With volume control for each channel. • AF output (using XLR sockets for separate output and mixed output).	Place of Share of Sha	18200

Note: All Prices Not Including VAT

